

DATA BLAD

JP-DL PL-xxx-x-xxx-x



Produkt Specifikation:

Dimension:	300x300x20, 300x600x20, 600x600x20, 300x1200x20
Vikt:	1.8 - 7.5kg
Material:	Aluminium/plast
Lamphus:	Fast
Montage	Infälld, Wire eller kundanpassad
LED Färg:	RGB, RGB-Y, Vit eller Varmvit
Ljusspridning:	120°
LED Panel Effekt:	14W, 33W, 56W.
Ljustyrka:	

Storlek	Vit	Varmvit
300x300	960lm	840lm
300x600	2100lm	1850lm
600x600	2100lm	1850lm
300x1200	3840lm	3360lm

Drivspänning:	24Vdc, Dimbar (PWM), Fjärrkontroll.
Antal LED:	60, 132, 240
Operativ Temp:	-20° ↔ +45° Celsius
Typisk livslängd	≤ 50.000 timmar
Garanti:	24mån
Övrigt:	

- ✚ Avger ingen UV eller IR strålning, Flimmerfri, Ljudlös.
- ✚ Gedigen konstruktion i Aluminium/Plast för bästa hållbarhet
- ✚ Endast 20mm hög.
- ✚ Stöder panelgrupper upp till 225 med 1 kontrollenhet.

JP International Technologies AB



Tel: 08-611 41 20
E-post: info@jptech.se
Web: www.jptech.se